

Product Data Sheet

SoSafe™ Professional (Red) Graffiti Remover - for professionals

Ideal to remove graffiti from: Brick, concrete, blocks, sheet metal, train exteriors, mortar, grout, marble, granite, slate, stone, stucco, unpainted shutters, terracotta, terrazzo, pebblecrete, pavers and other difficult to remove graffiti stains.

Product Description

SoSafe™ Professional is the latest edition to the So Safe range of graffiti removers. Professional edition has been specifically formulated for use by professionals with pressure cleaning equipment.

Unlike Blue and Yellow graffiti remover, Professional graffiti remover is not deactivated by water. The advantage of this is that it can be used immediately after pressure cleaning to give a deeper clean.

For particularly difficult graffiti stains i.e. shadows, Professional should be used in conjunction with So Safe Shadow Chaser (*see application section for details*). This process will eliminate all stains and graffiti shadows. It should be noted that the So Safe Professional will leave the surfaces with a 'wet' appearance for up to a couple of days after treatment; this illustrates how deep the chemical is penetrating the substrate and is not permanent.

NOTE: Some contractors prefer to leave Professional Edition on light shadows overnight to fade out shadows when used on sandstone and other erodible surfaces.

Characteristics

- * pH Neutral
- * Non-Flammable
- * Non-Hazardous
- * Biodegradable
- * Non-toxic
- * Non-Corrosive
- * Non-Water Neutralised

Tools / Equipment

To remove graffiti from difficult surfaces quickly it is recommended to have high pressure available, it is still possible to achieve great results without high pressure washing, though a little more time maybe required.

- * Gloves
- * Chemical Goggles
- * Applicator (Sprayer / Paint Brush / Roller)
- * High Pressure Washer
- * Graffiti Remover

Safety

When using graffiti remover follow safety directions on the label, wear appropriate attire including - enclosed

shoes, gloves and non-vented goggles.

Application Procedure

1. Dry surface is preferable, however product will work on damp surface.
2. Apply product by sprayer, paintbrush or roller.
3. Wait a minimum of 3 minutes.
4. Should the graffiti be difficult or not releasing, apply Shadow Chaser directly over the top of the graffiti remover with:

SMALL AREAS – Use paintbrush using a small container Shadow Chaser, keep your wrist down while applying, so not to have product run down your glove, do not spray.

LARGE AREAS – Use paint roller and tray, apply slowly (take care not to come into direct contact with Shadow Chaser), do not spray (follow label application and safety directions) **NOTE: Apply Shadow Chaser with care, follow all safety procedures. DO NOT SPLASH.**

5. Leave Shadow Chaser for a minimum of 4 minutes.
6. Remove chemicals with a high-pressure water blaster (hot water preferable), working slowly back facing the wind at a 45° angle at 3000psi for hard surfaces or < 900 psi on erodible surfaces.

Product Coverage

Coverage rates for graffiti removal vary significantly depending on various factors such as: age of the graffiti, type of graffiti, thickness of the graffiti, temperature, moisture, porosity, substrate and equipment used. A typical spray paint tag 1 metre x 2 metres on a brick wall will require approximately 400mLs to 1 Litre of product.

Pack Sizes

12x750mL (Retail Only) / 10x1Lt / 3x5Lt / 25Lt

Disclaimer

To the best of our knowledge and belief, the information is true and accurate at the time of publication. Since the conditions of use are out of the agents / distributors / manufacturers control, the end user must satisfy themselves by prior testing the product is suitable for their specific application.